


Drones and AI



What happens **NEXT** is happening **NOW**.

Brendan Brown, PWS

November 2025

 sky wave[®] at 

There is a 400,000 to 800,000 position deficit each year in our industry.

The US Needs More Engineers. What's the Solution?

By Abhi Kodey, [Julie Bedard](#), [Jonathan Nipper](#), Nancy Post, Sibley Lovett, and [Adriann Negreros](#)

BCG

ARTICLE DECEMBER 13, 2023 15 MIN READ



<https://www.bcg.com/publications/2023/addressing-the-engineering-talent-shortage>

There are multiple ways to leverage AI in our industry.


Administrative AI



Writing Reports



Conducting Research



LLMs progress has reached a performance plateau.




Administrative AI



Writing Reports



Conducting Research



Technical AI will transform the industry; there is room for unprecedented growth.


Administrative AI




Writing Reports



Conducting Research



Technical AI




Predictive Modeling



Data Analysis



CDM Smith is leveraging AI to drive data to decisions.



CDM Smith is leveraging AI to drive data to decisions.



Monitoring
Marsh Restoration

Mangrove and Seagrass
Monitoring


Mapping Exotic Species



AI models are used to make predictions based on input data.



Modern-day computer processing power has opened the door to widespread use of AI.




Modern-day computer processing power has opened the door to widespread use of AI.



Machine learning models are used to predict values or variables of interest based on input data.

Model Variables




Target Variable




Machine learning models are used to predict values or variables of interest based on input data.


Model Variables




Target Variable



Machine learning models require training data and validation data.




Training data is then used to train the machine learning model.





Model predictions are then compared to data of known values to determine model accuracy.


**DATA
INPUTS**




**MACHINE
LEARNING MODEL**



**MODEL
PREDICTIONS**



Model predictions are then compared to data of known values to determine model accuracy.



Lets start our adventure!




CDM Smith monitored a nature-based solution project at the mouth of the Savannah River.




CDM Smith monitored a nature-based solution project at the mouth of the Savannah River.



Marsh Restoration






Structure from Motion (SfM) can be used to generate 3D models from 2D images.

Sunlight




Drone data revealed that the contractor graded too high.



Areas out of spec for target grading



Multispectral data provides information vegetative cover and health.




Source: NASA

High resolution pixels identify individual *Spartina* plugs.

Fractional Vegetation Coverage (FVC)

$$\frac{NDVI - NDVI_{soil}}{NDVI_{veg} - NDVI_{soil}}$$




NDVI of Target


NDVI_{veg}
(100%)

NDVI_{soil}
(100%)

- Mitigation Area
- Reference Area



CDM Smith combined field data, 3D drone data, and multispectral data in a machine learning model to quantify biomass.



In [29]:


plot	min_h	p5_h	p25_h	p50_h	p75_h	p90_h	max_h	mean_h	std_h	...	ndvi_std	ndviPV
0 SM1	1.374916	1.441972	1.710196	2.045476	2.243596	2.362468	2.441716	1.954036	0.440293	...	0.031970	12.0
0 SM2	0.000000	0.000000	0.978388	4.090376	11.999936	16.660328	21.433496	7.354360	7.499678	...	0.024759	16.0
0 SM3	0.765338	0.853730	1.207298	1.649258	2.091218	2.356394	2.533178	1.649258	0.883920	...	0.033537	9.0
0 SM4	8.781973	8.832265	9.033433	9.803053	10.984153	11.875693	12.470053	10.214533	1.450765	...	0.043940	16.0
0 SM5	0.000000	0.137490	1.509493	7.605493	12.246073	13.015693	14.112973	7.084212	5.344436	...	0.034234	16.0
...
0 NN2	0.000000	0.000000	0.000000	0.000000	2.771751	12.610695	19.169991	4.388349	7.468375	...	0.019852	0.0
0 NN3	0.000000	1.197049	3.419342	7.899902	13.233902	16.275806	16.739102	8.522429	5.627527	...	0.020292	0.0
0 SN1	3.710798	3.791570	4.114658	4.518518	4.922378	5.164694	5.326238	4.518518	0.807720	...	0.015117	0.0
0 SN2	0.476578	1.112086	3.654118	5.261938	5.848678	5.917258	5.962978	4.240858	2.226136	...	0.020728	0.0
0 SN3	0.000000	0.000000	0.000000	0.000000	0.778743	1.245988	1.557485	0.519162	0.734206	...	0.009841	0.0

86 rows x 43 columns




The machine learning model can output site wide biomass.


2021




2022



Above Ground Biomass
(g/0.25m*0.25m)





Random Forest AGB (g/0.25m*0.25m)



Machine learning model results allow for easy identification of biomass loss and gain over time.

Change from 2021 to 2022





CDM Smith used drone data and machine learning used to monitor multiple ecosystems in Vero Beach, Florida.



Seagrass



Red Mangrove



Australian Pine (invasive)



CDM Smith used 10-band multispectral sensors to map the site.



Inspire 2 Drone



Flight Path




Drone-derived Aerial




10-band Dual Camera


Multispectral drones can monitor 100s of acres of seagrass at high resolution.




CDM Smith developed learning models to map seagrass/SAV versus sandy substrate.




Red mangroves have a different spectral signature than Australian pine which allows for machine learning-based mapping and monitoring.




Reflectance (%)



Australian Pine



Red Mangrove



Not visable to human eye

Wavelength

CDM Smith developed a machine learning model with over 95% accuracy to identify the invasive species Australian pine.



Australian Pine

Drones and machine learning can fill the gap between field transects and plane-based mapping.

Plane-based Mapping



Image: Courtesy of SurvTech

High-resolution/Efficient Collection



Time-consuming Field Transects



CDM Smith used machine learning to map exotic and native species and help Hillsborough County evaluate fire risk.



The wildland urban interface presents land management challenges.



Advanced remote sensing and AI provides better data to decisions makers.



100-acre Little Manatee River Site

Exotic Species

Biodiversity

Vegetative Cover

Vegetative Health

CDM Smith developed patent-pending data collection methods to increase efficiency and improve model accuracy.



CDM Smith created high-resolution 10-band orthophotographs.

False Color Composite Aerial with Near-infrared





Image Resolution
3-in per pixel




Machine learning can use spectral patterns to identify species.



CDM Smith developed a high accuracy map of native and exotic species using machine learning.

Overall machine learning model accuracy: > 80%




Pixel size = 3 inches

Class	★	★	★	★	★
★ andro	★ cogon	★ laurel	★ prax	★ skunk	★ smut
★ bahia	★ dog	★ live	★ rag	★ wire	★ smut
★ berm	★ euka	★ musc creep	★ rubus	★ bare1	★ bare2
★ caesar	★ guinea	★ natal	★ salt	★ sawpalm	
	★ hetero	★ oak	★ sandlive		
	★ jcw	★ per			

★ Exotic/Fire Species


★ Native/Fire Species

Machine learning model results can be used to pinpoint locations of exotic and native fire species.





 **Exotic/Fire Species**

 **Native/Fire Species**






Subject matter experts play a vital role in AI model development and accurate interpretation of predictions.





Subject matter experts play a vital role in AI model development and accurate interpretation of predictions.


Wetlands



Exotic Species



Sky Wave at CDM Smith leverages advanced remote sensing, automation, and AI to develop environmental solutions.



Contact:
skywave@cdmsmith.com



PATENT-PENDING DATA COLLECTION METHODS

 sky wave[®] at 

IDEAS


The Age of De-Skilling

Will AI stretch our minds—or stunt them?

By Kwame Anthony Appiah



Scan for more information



 sky wave[®] at 

Case Study: Remedial Excavation and Capping Jacksonville, FL



CDM Smith used automation and machine learning to monitor excavation and verify cap placement at a remediation site.

■ Objectives

- Track contractor performance
- Earth volume measurement
- Compliance

■ Location

- Ribault River, Jacksonville, FL




■ Size

- 50 acres

■ Sensors




Phase I of the remediation included excavation of 2 feet and capping with clean fill.



High resolution cameras are used to collect digital imagery of the site monthly.



High resolution aerial imagery documents site conditions.




Imagery can be used to assess contractor performance.




A 3D model is created for the site from each monthly drone flight.

Drone-derived 3D Model




CDM Smith uses automation to track topographic changes over time.




February



March




April




Elevation Change

> 1.5ft decrease	-0.499 - -0.25	0.751 - 1
-1.499 - -1.25	-0.249 - 0	1.001 - 1.25
-1.249 - -1	0.001 - 0.25	1.251 - 1.5
-0.999 - -0.75	0.251 - 0.5	> 1.5ft increase
-0.749 - -0.5	0.501 - 0.75	

The drone data is used to guide field efforts and verification sampling.




Random samples
apportioned by elevation change



Drone data can be used to assess BMPs.



Drone data can be used to assess BMPs.



After capping wetland trees were planted in a portion of the site to comply with state and federal permit requirements.




After capping wetland trees were planted in a portion of the site to comply with state and federal permit requirements.




Phase I = 470 trees
Phase II = 1,370 trees
Total = 1,840 trees




Ground truthing data was collected for use in a machine learning model.




Multispectral sensor collects near-infrared and provides data on vegetation.



The spectral signatures are often different between species.




Reflectance (%)



Red Maple



Holly




Not visible to human eye

Wavelength


CDM Smith used a machine learning model to identify tree species in the restoration area.



MACHINE LEARNING MODEL



MODEL PREDICTIONS



Holly



Cypress





Red Maple



Oak

Digital data, automation, and machine learning provide multiple project benefits.




Contractor Performance



Site Documentation



Permit Compliance





Restoration Monitoring



Case Study: Solar Site Feasibility and Wetland Mapping



CDM Smith used deep learning to evaluate the extent of uplands and wetlands in support of solar site feasibility.




■ Size

- 4 sites
- Total of 7,000 acres



■ Sensors



Wetlands and other Waters of the US regulations are in constant flux.



Field work crucial, but limiting, time-consuming, and hazardous.



Remote sensing data provides information that can be used to predict wetland presence with AI models.






Vegetation



Hydrology




Soils




There are multiple advantages of using lidar data.

Extra data





Details on Vegetation



Site Access Not Required


CDM Smith developed a machine learning model to map streams and wetlands.

Wetland Predictions





CDM Smith's deep learning model increased accuracy and ability to transfer the model to new sites.

Machine Learning Model





Deep Learning Model



CDM Smith's deep learning model increased accuracy and ability to transfer the model to new sites.


Deep Learning Model




The model results drastically reduce field time for delineations and provide high accuracy results for planning projects.



Wetlands and other Waters of the US regulations are in constant flux.



Field work crucial, but limiting, time-consuming, and hazardous.



Remote sensing data provides information that can be used to predict wetland presence with AI models.






Vegetation



Hydrology




Soils




There are multiple advantages of using lidar data.

Extra data





Details on Vegetation



Site Access Not Required

Remote sensing data provides information that can be used to predict wetland presence with AI models.



Wetland and Stream Predictions



The model results drastically reduce field time for delineations and provide high accuracy results for planning projects.

Deep Learning Model Results



+



=

